

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard (29 CFR 1910.1200)

Revision Date 18-Jul-2024 Version 12

1. IDENTIFICATION

Product identifier

Product Name HIGH TEMPERATURE THREAD SEALANT 50ML

Other means of identification

Product Code 59235

Recommended use of the chemical and restrictions on use

Recommended Use Sealant

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

ITW Permatex, Inc. 6875 Parkland Blvd. Solon, Ohio 44139 USA Telephone: 1-87-Permatex

(866) 732-9502

May Also Be Distributed by:

ITW Permatex Canada 101-2360 Bristol Circle

Oakville, ON Canada L6H 6M5 Telephone: (800) 924-6994

Company Phone Number 866-732-9502

24-hour emergency phone number

Chem-Tel: 800-255-3924 International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address: mail@permatex.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 2

Label elements

Emergency Overview

Signal word

Danger

Causes skin irritation

Causes serious eve irritation

May cause cancer

May cause damage to organs through prolonged or repeated exposure



Appearance White

Physical state Paste / Gel Liquid

Odor Mild

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Wear eve/face protection

Do not breathe dust/fume/gas/mist/vapors/spray

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash before reuse

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Harmful to aquatic life with long lasting effects. Harmful to aquatic life.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Weight-%
DIMETHYLBENZYL	80-15-9	1 - <2.5%
HYDROPEROXIDE		

Revision Date 18-Jul-2024

TITANIUM DIOXIDE	13463-67-7	0.5 - <1%
CUMENE	98-82-8	0.1 - <0.5%
TETRASODIUM EDTA	64-02-8	0.1 - <0.5%

4. FIRST AID MEASURES

Description of first aid measures

General advice If symptoms persist, call a physician.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms

persist, call a physician.

Skin contact Immediate medical attention is not required. Wash off immediately with soap and plenty of

water while removing all contaminated clothes and shoes. If skin irritation persists, call a

physician.

Inhalation Immediate medical attention is not required. If symptoms persist, call a physician. Move to

fresh air in case of accidental inhalation of vapors or decomposition products.

Ingestion Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth

to an unconscious person. Call a physician. Do NOT induce vomiting.

Self-protection of the first aiderUse personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use, Use dry chemical, Carbon dioxide (CO2), Water spray (fog), Alcohol resistant foam

Unsuitable extinguishing media

None

Specific hazards arising from the chemical

Keep product and empty container away from heat and sources of ignition. Risk of ignition.

Explosion data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Remove all sources of ignition. Pay attention to flashback. Take precautionary measures

against static discharges. Use personal protective equipment as required.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

See section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Use personal protective equipment as required. Dam up. Cover liquid spill with sand, earth

or other non-combustible absorbent material. Take up mechanically, placing in appropriate containers for disposal. Clean contaminated surface thoroughly. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Take precautionary

measures against static discharges.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Use with local exhaust ventilation. All equipment used when handling the product must be

grounded. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapors).

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, well-ventilated place. Store locked up. Keep away

from heat. Keep in properly labeled containers.

Incompatible materials Strong oxidizing agents, Amines

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
TITANIUM DIOXIDE	TWA: 0.2 mg/m³ nanoscale	TWA: 15 mg/m ³ total dust	IDLH: 5000 mg/m ³
13463-67-7	respirable particulate matter	(vacated) TWA: 10 mg/m ³ total dust	TWA: 2.4 mg/m ³ CIB 63 fine
	TWA: 2.5 mg/m ³ finescale		TWA: 0.3 mg/m ³ CIB 63 ultrafine,
	respirable particulate matter		including engineered nanoscale
CUMENE	TWA: 5 ppm	TWA: 50 ppm	IDLH: 900 ppm
98-82-8		TWA: 245 mg/m ³	TWA: 50 ppm
		(vacated) TWA: 50 ppm	TWA: 245 mg/m ³
		(vacated) TWA: 245 mg/m ³	
		(vacated) Sk*	
		Sk*	

NIOSH IDLH Immediately Dangerous to Life or Health

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Skin and body protection Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as Respiratory protection

appropriate.

General Hygiene Considerations When using do not eat, drink or smoke. Regular cleaning of equipment, work area and

clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state Paste / Gel Liquid

Appearance White Mild Odor

Odor threshold No information available

Property Values Remarks • Method

pН No information available No information available Melting point / freezing point > 200 °C / > 392 °F Boiling point / boiling range 131 °C / 268 °F Flash point **Evaporation rate** No information available Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit: No information available Lower flammability limit: No information available

<39.8 mm Hg Vapor pressure

Vapor density No information available

Relative density 1.16-1.26

Water solubility Immiscible in water No information available Solubility(ies) Partition coefficient No information available **Autoignition temperature** No information available Hyphen No information available Kinematic viscosity No information available Dynamic viscosity No information available

No information available **Explosive properties Oxidizing properties** No information available

Other information

Softening point No information available Molecular weight No information available

13.34% **VOC** content

Density No information available **Bulk density** No information available SADT (self-accelerating No information available

decomposition temperature)

10. STABILITY AND REACTIVITY

Reactivity

No information available

Chemical stability

Stable under normal conditions

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Excessive heat. Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents, Amines

Hazardous decomposition products

Carbon oxides

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation May cause damage to organs through prolonged or repeated exposure if inhaled.

Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact May cause skin irritation and/or dermatitis.

Ingestion Ingestion may cause irritation to mucous membranes.

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
DIMETHYLBENZYL HYDROPEROXIDE	= 382 mg/kg (Rat)	= 0.126 mL/kg (Rabbit)	= 220 ppm (Rat) 4 h
80-15-9			
TITANIUM DIOXIDE 13463-67-7	> 10000 mg/kg (Rat)	-	= 5.09 mg/L (Rat)4 h
CUMENE 98-82-8	= 1400 mg/kg (Rat)	= 12300 μL/kg (Rabbit)	> 3577 ppm (Rat) 6 h
TETRASODIUM EDTA 64-02-8	= 1658 mg/kg (Rat)	-	-

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization Germ cell mutagenicityNo information available.
No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
TITANIUM DIOXIDE	A3	Group 2B	-	X
13463-67-7				
CUMENE	A3	Group 2B	Reasonably Anticipated	X
98-82-8		-		

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not classifiable as a human carcinogen

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen
Occupational Safety and Health Administration of the US Department of Labor

X - Present

Target organ effects Respiratory system.

Revision Date 18-Jul-2024

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 15776 mg/kg
ATEmix (dermal) 28813 mg/kg
ATEmix (inhalation-dust/mist) 50.1 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

0.671 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical name	Partition coefficient
DIMETHYLBENZYL HYDROPEROXIDE	1.6
80-15-9	
CUMENE	3.55
98-82-8	

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number U055 U096

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste Status
DIMETHYLBENZYL HYDROPEROXIDE	Toxic
80-15-9	Ignitable
CUMENE	Toxic
98-82-8	Ignitable

14. TRANSPORT INFORMATION

DOT

Proper shipping name Not regulated

IATA

Proper shipping name Not regulated

IMDG

Proper shipping name Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies DSL/NDSL Complies Does not comply **EINECS/ELINCS ENCS** Complies **IECSC** Complies **KECI** Complies **PICCS** Does not comply **AICS** Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	SARA 313 - Threshold Values %
DIMETHYLBENZYL HYDROPEROXIDE - 80-15-9	1.0
CUMENE - 98-82-8	0.1

SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard No
Fire hazard No
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
DIMETHYLBENZYL HYDROPEROXIDE 80-15-9	10 lb	-	RQ 10 lb final RQ RQ 4.54 kg final RQ
CUMENE 98-82-8	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65
TITANIUM DIOXIDE	*Carcinogen (airborne, unbound particles of respirable size)
13463-67-7	
CUMENE	Carcinogen
98-82-8	-

^{• *}The asterisked chemical(s) listed are not subject to Proposition 65 because they are not airborne in the finished product **U.S. State Right-to-Know Regulations**

Chemical name	New Jersey	Massachusetts	Pennsylvania
POLYTETRAFLUOROETHYLENE 9002-84-0	-	-	X
SACCHARIN 81-07-2	Х	X	X
TITANIUM DIOXIDE 13463-67-7	X	X	X
CUMENE 98-82-8	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

D2B - Toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 1 Instability 0 -

HMIS Health hazards 2 Flammability 1 Physical hazards 0 Personal protection B

Revision Date 18-Jul-2024

Disclaimer

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of theinformation. User is responsible for evaluating whether such information or this product is fit for a particular purposeand suitable for a particular use or application. The information in this data sheet may not be valid if this product is usedin combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims anyliability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of thisproduct. Ensure you have the most current version of this data sheet by contacting us or reviewing our web

End of Safety Data Sheet