

# **SAFETY DATA SHEET**

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard (29 CFR 1910.1200)

Revision Date 30-May-2024 Version 10

## 1. IDENTIFICATION

**Product identifier** 

Product Name 767 ANTI-SEIZE LUBRICANT 1LB

Other means of identification

Product Code 80208

Recommended use of the chemical and restrictions on use

Recommended Use Lubricant

Uses advised against No information available

#### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

ITW Permatex, Inc. 6875 Parkland Blvd. Solon, Ohio 44139 USA Telephone: 1-87-Permatex

(866) 732-9502

#### May Also Be Distributed by:

ITW Permatex Canada 101-2360 Bristol Circle

Oakville, ON Canada L6H 6M5 Telephone: (800) 924-6994

#### 24-hour emergency phone number

Chem-Tel: 800-255-3924 International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address: mail@permatex.com

# 2. HAZARDS IDENTIFICATION

## Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity Category 1B

## Label elements

# **Emergency Overview**

## Signal word Danger

May cause cancer



Appearance Silver Physical state Paste / Gel Liquid Odor Petroleum

# **Precautionary Statements - Prevention**

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product

### **Precautionary Statements - Response**

If exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water If skin irritation occurs: Get medical advice/attention

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

## **Precautionary Statements - Storage**

Protect from sunlight. Store in a well-ventilated place Store locked up

## **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

## Hazards not otherwise classified (HNOC)

Not applicable

## **Other Information**

Very toxic to aquatic life.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Weight-%
Almandite-Ferric Aluminum Silicate	1302-62-1	25 - <50%
MINERAL OIL	8042-47-5	25 - <50%
DISTILLATES (PETROLEUM),	64742-52-5	10 - <25%
HYDROTREATED HEAVY		
NAPHTHENIC		
ALUMINIUM POWDER	7429-90-5	5 - <10%
GRAPHITE	7782-42-5	2.5 - <5%
PARAFFIN OILS (PETROLEUM),	64742-71-8	1 - <2.5%
CATALYTIC DEWAXED LIGHT		

# 4. FIRST AID MEASURES

**Description of first aid measures** 

General advice If symptoms persist, call a physician.

**Eye contact** Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms

persist, call a physician.

**Skin contact** Immediate medical attention is not required. Wash off immediately with soap and plenty of

water while removing all contaminated clothes and shoes. If skin irritation persists, call a

physician.

**Inhalation** Immediate medical attention is not required. If symptoms persist, call a physician. Move to

fresh air in case of accidental inhalation of vapors or decomposition products.

Ingestion IF SWALLOWED:. Call a POISON CENTER or doctor/physician if you feel unwell. Rinse

mouth. Clean mouth with water and drink afterwards plenty of water. Never give anything by

mouth to an unconscious person. Call a physician. Do NOT induce vomiting.

**Self-protection of the first aider**Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

**Symptoms** See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

**Note to physicians**Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use, Use dry chemical, Carbon dioxide (CO2), Water spray (fog), Alcohol resistant foam

Small Fire In case of fire, use water spray, foam, dry chemical, or CO2.

Large Fire In case of fire, use water spray, foam, dry chemical, or CO2.

Unsuitable extinguishing media

Water

Specific hazards arising from the chemical

Keep product and empty container away from heat and sources of ignition. Risk of ignition.

Hazardous combustion products No information available.

**Explosion data** 

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes and skin. Wash thoroughly after handling. Use personal protective

equipment as required. Evacuate personnel to safe areas. Keep people away from and

upwind of spill/leak. Remove all sources of ignition. Pay attention to flashback. Take precautionary measures against static discharges.

Environmental precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

See section 12 for additional ecological information.

Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Use personal protective equipment as required. Dam up. Cover liquid spill with sand, earth

or other non-combustible absorbent material. Take up mechanically, placing in appropriate containers for disposal. Clean contaminated surface thoroughly. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Take precautionary

measures against static discharges.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

#### 7. HANDLING AND STORAGE

#### Precautions for safe handling

grounded. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapors).

#### Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat. Keep

in properly labeled containers.

Incompatible materials No information available

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Control parameters

**Exposure Guidelines** 

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
ALUMINIUM POWDER	TWA: 1 mg/m³ respirable	TWA: 15 mg/m³ total dust	TWA: 10 mg/m <sup>3</sup> total dust
7429-90-5	particulate matter	TWA: 5 mg/m³ respirable fraction	TWA: 5 mg/m <sup>3</sup> respirable dust
		(vacated) TWA: 15 mg/m <sup>3</sup> total dust	TWA: 5 mg/m³ Al
		(vacated) TWA: 5 mg/m <sup>3</sup> respirable	
		fraction	
		(vacated) TWA: 5 mg/m³ Al	
		Aluminum	
GRAPHITE	TWA: 2 mg/m <sup>3</sup> respirable	TWA: 15 mg/m³ total dust	IDLH: 1250 mg/m <sup>3</sup>
7782-42-5	particulate matter all forms except	synthetic	TWA: 2.5 mg/m³ natural respirable
	graphite fibers	TWA: 5 mg/m³ respirable fraction	dust
		synthetic	
		TWA: 15 mppcf respirable dust	
		natural	
		(vacated) TWA: 2.5 mg/m <sup>3</sup>	
		respirable dust natural	
		(vacated) TWA: 10 mg/m³ total dust	
		synthetic	
		(vacated) TWA: 5 mg/m³ respirable	
		fraction synthetic	

TWA: 15 mppcf natural

NIOSH IDLH Immediately Dangerous to Life or Health

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

**Eye/face protection** Tight sealing safety goggles.

Skin and body protection Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

appropriate.

General Hygiene Considerations When using do not eat, drink or smoke. Regular cleaning of equipment, work area and

clothing is recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Air = 1

9.1. Information on basic physical and chemical properties

Physical state Paste / Gel Liquid

Appearance Silver
Odor Petroleum
Color Gray

Odor threshold No information available

Property Values Remarks • Method

pH No information available
No information available
No information available
No information available

Flash point > 95 °C / > 203 °F Tag Closed Cup Evaporation rate < 1 Butyl acetate = 1

Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit: No information available
Lower flammability limit: No information available

Lower flammability limit: No information available Vapor pressure <5 mm Hg

Vapor density >1 Relative density 1.41-1.51

Water solubility

Solubility(ies)

Negligible
No information available

Partition coefficientNo information availableAutoignition temperatureNo information availableHyphenNo information availableKinematic viscosityNo information availableDynamic viscosityNo information availableExplosive propertiesNo information available

Explosive propertiesNo information availableOxidizing propertiesNo information available

Other information

Softening pointNo information availableMolecular weightNo information availableDensityNo information available

Bulk density 자료 없음

SADT (self-accelerating No information available

decomposition temperature)

## 10. STABILITY AND REACTIVITY

Reactivity

No information available

Chemical stability

Stable under normal conditions

Possibility of hazardous reactions

None under normal processing.

**Hazardous polymerization** 

No information available.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

No information available

Hazardous decomposition products

Carbon oxides

# 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

**Inhalation** May cause irritation of respiratory tract.

Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

**Skin contact** May cause skin irritation and/or dermatitis.

**Ingestion** Harmful if swallowed.

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
MINERAL OIL 8042-47-5	> 5000 mg/kg (Rat)	-	-
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC 64742-52-5	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	-
ALUMINIUM POWDER 7429-90-5	-	-	> 0.888 mg/L (Rat)4 h
GRAPHITE 7782-42-5	-	-	> 2000 mg/m³ (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Irritating to skin.
Serious eye damage/eye irritation Irritating to eyes.
Sensitization

**Sensitization Germ cell mutagenicity**No information available.
No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
DISTILLATES	A2	Group 1	Known	X

**Revision Date** 30-May-2024

(PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC 64742-52-5				
PARAFFIN OILS (PETROLEUM), CATALYTIC DEWAXED LIGHT 64742-71-8	A2	Group 1	Known	Х

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 3 - Not classifiable as a human carcinogen

NTP (National Toxicology Program)

Known - Known Carcinogen

Occupational Safety and Health Administration of the US Department of Labor

X - Present

Developmental ToxicityNo information available.TeratogenicityNo information available.Neurological effectsNo information available.Other adverse effectsNo information available.

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 1991 mg/kg
ATEmix (dermal) 23171 mg/kg
ATEmix (inhalation-dust/mist) 6.7 mg/l
ATEmix (inhalation-vapor) 32255 mg/l

## 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

## Persistence and degradability

No information available.

## **Bioaccumulation**

No information available.

#### **Mobility**

No information available.

Chemical name	Partition coefficient
MINERAL OIL	6
8042-47-5	

#### Other adverse effects

No information available

## 13. DISPOSAL CONSIDERATIONS

## Waste treatment methods

**Disposal of wastes**Disposal should be in accordance with applicable regional, national and local laws and

regulations.

**Contaminated packaging** Do not reuse container.

US EPA Waste Number Not applicable

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste Status
ALUMINIUM POWDER	Ignitable powder
7429-90-5	- '

## 14. TRANSPORT INFORMATION

DOT

Proper shipping name Not regulated

**IATA** 

Proper shipping name Not regulated

MDG

Proper shipping name Not regulated

# 15. REGULATORY INFORMATION

**International Inventories** 

**TSCA** Complies Complies DSL/NDSL Complies **EINECS/ELINCS** Does not comply **ENCS IECSC** Complies Complies KECI Complies **PICCS AICS** Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

## **US Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	SARA 313 - Threshold Values %
ALUMINIUM POWDER - 7429-90-5	1.0
SARA 311/312 Hazard Categories	
Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

#### **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

## **US State Regulations**

#### **California Proposition 65**

This product contains the following Proposition 65 chemicals:

# U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
ALUMINIUM POWDER	X	X	X
7429-90-5			
GRAPHITE	X	X	X
7782-42-5			
PARAFFIN OILS (PETROLEUM),	-	X	-
CATALYTIC DEWAXED LIGHT			
64742-71-8			

#### U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

#### **WHMIS Hazard Class**

D2A - Very toxic materials

# 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 1 Instability 0 -

HMIS Health hazards 2 Flammability 1 Physical hazards 0 Personal protection B

Revision Date 30-May-2024

#### **Disclaimer**

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However,Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of theinformation. User is responsible for evaluating whether such information or this product is fit for a particular purposeand suitable for a particular use or application. The information in this data sheet may not be valid if this product is usedin combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims anyliability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of thisproduct. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

**End of Safety Data Sheet** 

Page 9/9